

# Multi Grabs

IMG 10 H






Product **news**

 **INDECO**  
A TOOL FOR EVERY JOB

Thanks to the new jaw design, the hydraulic rotation system and the force transmitted to the opposing teeth, which guarantee a safe and powerful grip, the new Multi Grab IMG 10 H is the ideal tool for handling large objects, such as scrap metal, cars in the junkyard, demolition waste.



| Technical Data  | IMG 10 H  |
|---|---|
| Maximum working pressure  | 4400 psi  |
| Maximum oil delivery  | 13.5 gpm  |
| Hydraulic connections for cylinder  | 1/2"  |
| Maximum rotation pressure   | 1500 psi  |
| Maximum rotation oil flow   | 5.5 gpm   |
| Hydraulic connections for rotation  | 1/2"  |
| Maximum force at blade/teeth  | 11000 lbs   |
| Compatibility of attachment plate with hammer   | HP 1500   |
| Excavator weight  | 19800   |
|  (best) lbs      |  |
|  (possible) lbs* | 22000 35500   |

### Material Handling Jaws 3+2

|                               |          |
|-------------------------------|----------|
| Attachment operating weight** | 1900 lbs |
| Maximum opening               | 80 in    |
| Depth                         | 24 in    |

\*Suggested uses on machines with an overall weight (in lbs).

\*\*The operating weight of the equipment includes mounting bracket compatible with Indeco construction standards. Any differences in weight may be due to a different mounting bracket configuration.

The information in this catalog is subject to change without notice and without any obligation or responsibility on our part. The content of this catalog is provided as a courtesy to readers and constitutes non binding information only.