

Multi Grabs

IMG 10 H



Product **news**

Thanks to the new jaw design, the hydraulic rotation system and the force transmitted to the opposing teeth, which guarantee a safe and powerful grip, the new Multi Grab IMG 10 H is the ideal tool for handling large objects, such as scrap metal, cars in the junkyard, demolition waste.



Technical Data

IMG 10 H

Maximum working pressure	300 bar
Maximum oil delivery	50 l/min
Hydraulic connections for cylinder	1/2"
Maximum rotation pressure	100 bar
Maximum rotation oil flow	20 l/min
Hydraulic connections for rotation	1/2"
Maximum force at blade/teeth	5000 Kg
Compatibility of attachment plate with hammer	HP 1200
Excavator weight	9
 (best) ton	
 (possible) ton*	10 16

Material Handling Jaws 3+2

Attachment operating weight**	850 Kg
Maximum opening	1900 mm
Depth	600 mm

*Suggested uses on machines with an overall weight (ton).
**The operating weight of the equipment includes mounting bracket compatible with Indeco construction standards. Any differences in weight may be due to a different mounting bracket configuration.

The information in this catalog is subject to change without notice and without any obligation or responsibility on our part. The content of this catalog is provided as a courtesy to readers and constitutes non binding information only.