

Multi Grabs

IMG 10 H



Product **news**

 **INDECO**

ATTACHMENT SOLUTIONS

a wipro[®] hydraulics company

Thanks to the new jaw design, the hydraulic rotation system and the force transmitted to the opposing teeth, which guarantee a safe and powerful grip, the new Multi Grab IMG 10 H is the ideal tool for handling large objects, such as scrap metal, cars in the junkyard, demolition waste.



Technical Data

IMG 10 H

Maximum working pressure	4400 psi
Maximum oil delivery	13.5 gpm
Hydraulic connections for cylinder	1/2"
Maximum rotation pressure	1500 psi
Maximum rotation oil flow	5.5 gpm
Hydraulic connections for rotation	1/2"
Maximum force at blade/teeth	11000 lbs
Compatibility of attachment plate with hammer	HP 1500
Excavator weight	19800
 (best) lbs	
 (possible) lbs*	22000 35500

Material Handling Jaws 3+2

Attachment operating weight**	1900 lbs
Maximum opening	80 in
Depth	24 in

*Suggested uses on machines with an overall weight (in lbs).

**The operating weight of the equipment includes mounting bracket compatible with Indeco construction standards. Any differences in weight may be due to a different mounting bracket configuration.

The information in this catalog is subject to change without notice and without any obligation or responsibility on our part. The content of this catalog is provided as a courtesy to readers and constitutes non binding information only.