

Multiprocessor

IMP 15 Car Dismantler



Product **news**

A configuration designed to perfectly combine the various actions of cutting, separating, and handling materials for vehicle scrapping operations.



Technical Data

IMP 15 Car Dismantler

Width	425 mm
Oil delivery	150 ÷ 250 l/min
Maximum pressure at cylinders	350 bar
Closure time (no-load)	2 s
Opening time (no-load)	1 s
Hydraulic connections for cylinders	3/4"
Maximum rotation flow	20 l/min
Maximum rotation pressure	110 bar
Hydraulic connections for rotation	1/2"
Mounting bracket compatibility	HP 2000 - HP 2500
Excavator weight	12
<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #FFC000; margin-right: 5px;"></div> (best) ton </div>	<div style="width: 100px; height: 15px; background-color: #FFC000; position: relative;"> <div style="width: 100%; height: 100%;"></div> </div>
<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #808080; margin-right: 5px;"></div> (possible) ton* </div>	<div style="display: flex; align-items: center; gap: 10px;"> 14 24 </div>

JAW TECHNICAL DATA

Operating weight**	1500 Kg
Height	2350 mm
Maximum opening	1200 mm
Jaw depth	1050 mm
Cutter blade length	240 mm
Max clamping force at tip	35 ton
Maximum clamping force at shears	230 ton

*Suggested uses on machines with an overall weight (in ton).

**The operating weight of the equipment includes mounting bracket compatible with Indeco construction standards. Any differences in weight may be due to a different mounting bracket configuration.



INDECO ind S.p.a.

viale Lindemann, 10 z.i. - 70132 Bari - Italy

PH +39 080 531 33 70 - **F** +39 080 537 79 76

@ info@indec.it - www.indec.it/en